

09.8405.DY Matte White

Gustave Residential

Designed by Vincent Van Duysen, 2022



Gustave is a portable, self-powered luminaire, specially designed for tabletop lighting applications and other related uses as supplementary lighting. Gustave's compact size encloses a perfect mix of the most innovative optical and light technology and a disruptive engineering, developed in the service of a discretionary purpose of Flos for this project: to create the first portable luminaire on the market with circular design awareness, ecological and honestly conceived against obsolescence. Portable luminaire with autonomous battery, designed for residential applications. Powered by 'Button Type 18650 Li-lon' batteries (2 units, included inside the product). USB-C charging cable (plug adapter not included). 0-100% sequential regulation by means of capacitive haptic push button.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Table	
Light source type	LED	
Light sources included	Yes	
LED type	Top LED	
Lamp category	LED	
Number of lamps	1	
Power (W)	2.5	
System power (W)	2.5	
Source flux (lm)	221	
Lumen Output (lm)	159	
Efficacy (lm/W)	69	

Physical

Colour	Matte White	
Length (mm)	155	
Cord colour	Black	
Cord length (mm)	1200	
Net weight (kg)	0.78	
Package height (mm)	36	
Package width (mm)	21	
Package length (mm)	21	
Package volume (m3)	0.02	
IP internal	54	



Download

Mounting instructions



Photometric Files

LDT / IES




Technical Drawings

2D



Ecodesign and Energy Labelling








Replaceable control gear by an end-user

https://professional.flos.com/en/global/product/gustave-residential-09.8405.dy/

09.8405.DY

Schematic light drawing



Beam Angle:		145°
h(m)	E(lx)	D(m)
1	22	6.28
2	6	12.56
3	2	18.84
4	1	25.11
5	1	31.39

Luminous flux luminaire 159 lm

Photometric

Lighting type	Direct	
Light distribution	Roto symmetric	
CCT (K)	2700	
CRI>	90	
McAdam steps (SDCM)	3	
Rf fidelity index	93	
Rg gamut index	100	
Beam angle C0-180 (°)	144	
Beam angle C90-270 (°)	144	

Electrical

Insulation class	III	
LED current (mA)	180	
Dimmable	Yes	
Power supply type	Dimmable	
Dimming interface	Dimmer Integrated	
Plug type	Type A	
Batteries inside	Yes	
Battery type	LI-IO	
Charging cycles guaranteed	500	
Charging max power	1 A	
Charging min time	5.5	
Charging socket/connector	USB-C	

Notes

Product Battery autonomy: 100% - 6 hours / 50% - 10 hours / 25% - 18 hours. Batteries included. USB-A / USB-C Cable included. Adapter 5V, min 2A not included.

Accessories & Power Supply



REQUIRED

RF25965

Adapter 5V. Min 2A | EUR USA UK




REQUIRED

RF27576

Gaku Adapter 5V. Min 2A. EUR / USA / UK

Spare Parts



01.	Pack 2x Battery for Gustave	08.0744.00
	Residential	
02.	Cable for Gustave Residential	08.0761.14
	USB-A/USB-C	
02.	Cable for Gustave Residential	08.0761.30
	USB-A/USB-C	





08 0744 00

Pack 2x Battery for Gustave Residential



Cable

08.0761.14

Cable for Gustave Residential USB-A/USB-C



Cable

08.0761.30

Cable for Gustave Residential USB-A/USB-C